

Achievers Energy Solar Panel Series STP270-280 - 20 /Wfw. Detailed profile including pictures, certification details and manufacturer PDF ... STP275-20/ Wfw Warranty Product Warranty 12 Years ...

NOCT: Irradiance 800 W/m<sup>2</sup>, ambient temperature 20 °C, AM=1.5, wind speed 1 m/s; Best in Class AAA solar simulator (IEC 60904-9) used, power measurement uncertainty is within +/- 3% AU-STP-Wfj-NO2.01-Rev 2018 Electrical Characteristics STC STP275-20/ Wfj STP270-20/ Wfj STP265-20/ Wfj Maximum Power at STC (Pmax) 275 W 270 W 265 W

STP280 - 20/Wfw STP275 - 20/Wfw STP270 - 20/Wfw 0/+5W Positive tolerance Positive tolerance of up to 5 W delivers higher output reliability IP68 Rated Junction Box The Suntech IP68 rated junction box ensures an outstanding waterproof level, supports installations in all orientations and reduces stress on the cables. High reliable performance,

Suntech STP275-20/Wfw 275Wp De Suntech STP275-20/ Wfw is een polykristallijne zonnemodule met 275Wp. \* nieuwe en ongebruikte resterende voorraad \* Modules kunnen lichte sporen van opslag vertonen \* Vervangingsmodule voor bestaande systemen voor schadeafhandeling bij verzekeringsclaims! \* Prijs is per module \* Bezorgen of afhalen mogelijk

Big selection Suntech Power STP275-20/Wfw 275Wp275Wp - Solar Panel order now from Secondsol. Register. Sign-In. Username. Password. 2-Faktor Anmeldung. Nach der Eingabe Ihres Benutzernamens erhalten Sie einen ...

Maximum Series Fuse Rating 20 A Power Tolerance 0/+5 W STC: Irradiance 1000 W/m<sup>2</sup>, module temperature 25 °C, AM=1.5; Tolerances of Pmax, Voc and Isc are all within +/-5% NMOT STP285-20/ Wfm STP280-20/ Wfm STP275-20/ Wfm Maximum Power at NMOT (Pmax) 214.4 W 210.3 W 206.4 W Optimum Operating Voltage (Vmp) 29.8 V 29.5 V 29.2 V

STP275 - 20/Wfw Strom-Spannungs- & Leistungs- Spannungskennlinie (285) Mechanische Eigenschaften Solarzelle Polykristallines Silizium 6 Zoll Anzahl der Zellen 60 (6 x10) Abmessungen 1.650 x 992 x 35 mm (64,96 x 39,1 x 1,4 Zoll) Gewicht 18,3 kg Frontglas 3,2 mm (0,13 Zoll) gehärtetes Glas

STP275-285 - 20 /Wfw-TG Wuxi Suntech Power Co., Ltd. : : Wp : ?????? ?????????? ?????? VDS Renewable - VDS-S132/M12H 650-670W ...

Riesige Auswahl Suntech STP275-20/Wfw275Wp - PV-Module jetzt bei Secondsol bestellen. Registrieren. Anmelden. Benutzername. Passwort. 2-Faktor Anmeldung. Nach der Eingabe Ihres Benutzernamens erhalten Sie einen Code per E-Mail! ... STP275-20/Wfw 5.0 (123 Kundenrezensionen) 82,50 ...

## Stp275 20 wfw Turkmenistan

STP275 - 20/Wfw 5 PREMIUM Years WARRANTY Weak light Excellent weak light performance More power output in weak light condition, such as haze, cloudy, and morning lower hot spots Reduce the hot spots and minimize panel degradation \*\* Certifications and standards: IEC 61215, IEC 61730, conformity to CE

Suntech STP275-20/Wfw 275Wp . Das Suntech STP275-20/ Wfw ist ein polykristallines Solarmodul mit 275Wp. \* neuer und unbenutzter Restposten \* Module k&#246;nnen leichte Lagerspuren aufweisen \* Ersatzmodul f&#252;r bestehende Anlagen zur Schadensregulierung bei Versicherungsfall!

STP 275 - 20 / Wfw Suntech STP 275-20 / Wfw Projektowanie i montaz system&#243;w fotowoltaicznych, dystrybucja komponent&#243;w Mont&#225;ze s.r.o. ... STP275 - 20/Wfw, STP270 - 20/Wfw, STP265 - 20/Wfw. Dane moga ulec zmianie! Adres siedziby firmy:, U panelarny 10, 772 00 Olomuniec, Republika Czeska

20 A Leistungstoleranz 0/+5 W STC (Standardtestbedingungen): Strahlungsintensit&#228;t 1,000W/m<sup>2</sup>, Modultemperatur 25 &#176;C, Luftmasse=1,5. Bei Einsatz des f&#252;hrenden AAA-Solarsimulators (IEC60904-9) k&#246;nnen Messgenauigkeiten von &#177; 3 % erreicht werden. NOCT STP275-20/ Wfw STP270-20/ Wfw STP265-20/ Wfw Maximale Leistung unter NOCT (?m??) 202,6 W ...

Suntech Power STP275-20/Wfw (5BB) - polykristallines Hochleistungssolarmodul mit 275 Watt in 5 Busbar-Technologie Nennleistung: 275 W Leistungstoleranz: 0/+5W L&#228;nge x Breite x H&#246;he: 1650 x 992 x 35 mm Frontabdeckung: ...

STP275-285 - 20 /Wfw-TG Wuxi Suntech Power Co., Ltd. Technology: Power Range: Wp Region: China Contact Manufacturer Product is no longer manufactured. Solar Panel MY Solar - M10 Series MY-M10/144-540-560W From EUR0.0616 / Wp ...

Maximum Series Fuse Rating 20 A Power Tolerance 0/+5 W STC: Irradiance 1000 W/m<sup>2</sup>, module temperature 25 &#176;C, AM=1.5; Best in Class AAA solar simulator (IEC 60904-9) used, power measurement uncertainty is within +/- 3% NOCT STP285S-20/ Wfw STP280S-20/ Wfw STP275S-20/ Wfw Maximum Power at NOCT (Pmax) 210.4 W 206.5 W 202.8 W

NOCT: Irradiance 800 W/m<sup>2</sup>, ambient temperature 20 &#176;C, AM=1.5, wind speed 1 m/s; Best in Class AAA solar simulator (IEC 60904-9) used, power measurement uncertainty is within +/- 3% STP275- 20/Wfw STP270 - 20/Wfw STP265 - 20/Wfw Temperature Characteristics Nominal Operating Cell Temperature (NOCT) 45&#177;2&#176;C Temperature Coefficient of Pmax -0.41 %/&#176;C

NOCT: Irradiance 800 W/m<sup>2</sup>, ambient temperature 20 &#176;C, AM=1.5, wind speed 1 m/s; Best in Class AAA solar simulator (IEC 60904-9) used, power measurement uncertainty is within +/- 3% STP275- 20/Wfw STP270 - 20/Wfw STP265 - 20/Wfw Temperature Characteristics Nominal Operating Cell Temperature (NOCT) 45&#177;2&#176;C Temperature Coefficient of Pmax -0.41 ...

